



ISO Certificate Good UNS S30815 1.4835 Stainless Steel Metal Welding Wire 253MA

Our Product Introduction

for more products please visit us on victory-alloy.com

Basic Information

- Place of Origin: Jiangsu, China
- Brand Name: Victory
- Model Number: 200/300/400 series, 201/304/316/316L/410/416
- Minimum Order Quantity: 3 kilograms
- Price: \$6.00/kilograms 3-499 kilograms
- Packaging Details: stainless steel wire is packed with waterproof paper or weave bag, into carton boxes, pallets or wooden case. Special packaging requirements can also be accommodated. OEM is also acceptable.
- Supply Ability: 150 Ton/Tons per Month



Product Specification

- Standard: AISI
- Grade: 200/300/400 Series
- Length: Customize
- Application: Chemical Industry, Heating, Energy, etc
- C Content (%): ~0.25%
- Si Content (%): ~1.50%
- Tolerance: ±1%
- Processing Service: Bending, Welding, Decoiling, Punching, Cutting
- Steel Grade: 304, 314, 316L, 316Ti, 410, 430
- Surface Finish: BA
- Delivery Time: 15-21 Days
- Surface: Bright Or Matt
- Condition: Soft
- Is Powder Or Not: Not Power



More Images



Product Description

Grade: SUS316/316F/316L/304/304L/310/310S/303.201/202/303CU/303F/305/309/321/317, etc.

Advantage: Our range of Wire made of Stainless Steel are not only known for their variety but are also known for their good quality, long life and very reasonable prices. Quality and service is our first priority, we effectively use technically advanced machinery equipment and the expertise of our work to deliver our stainless steel wired products.

Shape	Size(mm)
Wire	0.05-7.5

Our Product Introduction

Rod	8-50
Ribbon	(0.05-0.35)*(0.5-6.0)
Strip	(0.5-2.5)*(5-180)

AISI Chemical composition table

C	Si	Mn	P	S	Ni	Cr	Mo
304	<0.08	<1.0	<2.0	<0.035	<0.03		8-10 17-19
304L	<0.03	<1.0	<2.0	<0.04	<0.03		9-13 18-20
304HC	<0.06	<1.0	1.2-1.8	<0.035	<0.03		8-11 17-19
316	<0.08	<1.0	<2.0	<0.04	<0.03		10-14 16-18
316L	<0.03	<1.0	<2.0	<0.04	<0.03		12-15 16-18
310S	<0.08	<1.5	<2.0	<0.04	<0.03	19-22	24-26
321	<0.08	<1.0	<2.0	<0.045	<0.03		9-13 17-19
301	<0.15	<1.0	<2.0	<0.04	<0.03	>7	16-18
302	<0.15	<1.0	<2.0	<0.04	<0.03	>8	17-

Stainless steel wire size tolerance

Wire diameter (mm)	Tolerance (mm)	Maximum deviation (mm)
0.-0.299	±0.005	0.005
0.300-0.310	±0.006	0.006
0.320-0.499	±0.006	0.006
0.500-0.599	±0.006	0.006
0.600-0.799	±0.008	0.008
0.800-0.999	±0.008	0.008
1.00-1.20	±0.009	0.009
1.20-1.40	±0.009	0.009
1.40-1.60	±0.010	0.01
1.60-1.80	±0.010	0.01
1.80-2.00	±0.010	0.01
2.00-2.50	±0.012	0.012
2.50-3.00	±0.015	0.015
3.00-4.00	±0.020	0.02
4.00-5.00	±0.020	0.02



Changzhou Victory Technology Co., Ltd

+8619906119641

victory@dlx-alloy.com

victory-alloy.com

NO.32 West Taihu Road, Xinbei District, Changzhou, Jiangsu